

PRODUCT DESCRIPTION

Fluorescent enamel paint specially formulated to be used on interior and exterior surfaces of wood, metal and fibreglass.

TECHNOLOGY

Fluorescent technology

ADVANTAGES

- Diffuses light; excellent for masking a number of imperfections.
- Ready for use and easy to apply.
- Dries quickly and has very little odour.
- Exceptional levelling and durability.

PROJECTS

USE

New and maintenance work.
Residential and commercial sites.

SURFACES

Surfaces of wood, metal and fibreglass.

ENVIRONMENT

Interior and exterior.

NOTES

- This product is not to be mixed with other paints or thinners.
- This product is not to be applied directly to bare ferrous metals (iron, steel).
- This product is not formulated to be used on floors.
- This product is not recommended for automobile use.

TECHNICAL SPECIFICATIONS (21°C (70°F))

Appearance	Opaque
Gloss Level	Flat finish • Gloss at 60°: 0 to 5% • Gloss at 85°: Not available
Composition	• Diluent: Hydrocarbons • Binder: Synthetic resins
Volatile Organic Compounds (VOCs)*	According to ASTM D3960-05: Not available Canadian standard: not applicable
Spreading Rate per Coat	Varies with surface porosity.
Recommended Film Thickness*	(according to the maximum spreading rate) • Wet: Not available • Dry: Not available
Solids by Volume*	Not available
Flammability	Extremely flammable

DRYING TIME*



- Touch dry: 2 minutes
- Before recoating: within 1 hour or after 48 hours
- Before cleaning: 7 days

When relative humidity is higher than 50%, double the required drying time.



*Technical data source: 635-715

SURFACE PREPARATION

Surfaces must be clean, solid, dry and free from dust, dirt, oil, soot, wax, mildew, chalking, loose paint, or other contaminants. In order to prepare surfaces adequately, follow the preparation steps as described below:

- ▶ Clean surface with Polyprep cleaner 771-135, 771-136, or the appropriate cleaner for removing the contaminant. Rinse thoroughly.
 - To remove mildew, wash with a solution of household bleach (1 part household bleach to 3 parts water). Wear rubber gloves and eye protection. Rinse thoroughly with clear water and let dry completely.
 - ▶ Repair holes and cracks with a paste filler or a joint compound suitable for the surface to be repaired.
 - If wood exudes resin, scrape the excess and clean surface with alcohol or paint thinner. On bare wood, seal knots and sap streaks with shellac before applying the primer.
 - ▶ Before applying the base coat, cover or mask surfaces that are not to be painted.
- Listed below are the main base coat products that are recommended:

APPLICATION CONDITIONS

Temperature: 10 to 32°C (50 to 90°F)
(ideal 20°C ± 5°C [68°F ± 9°F]).

Relative humidity: ideal between 15 and 50%, maximum 85%.

Surface must be at a temperature at least 3°C (5°F) higher than dew point. Do not apply under direct sunlight or during windy conditions.

Do not apply when lower temperatures are expected within 3 to 6 hours.

TOOLS

Spray can

CLEANING TOOLS

Remove as much of the product as possible and clean tools with Polyprep 875-104, 875-105 or mineral spirits immediately after use.

SURFACE MAINTENANCE

- Let surfaces dry completely and wait at least 7 days before cleaning them. Use a non-abrasive cleaner and a soft cloth.
- If required, prime and retouch bare areas, and apply an additional coat on the whole surface.

APPLICATION

This is a ready-to-use product, do not thin. Shake well before and frequently during use. Provide adequate ventilation. Apply at room temperature.

Protect surrounding finishes and articles by covering them.

Hold can upright 20 to 30 cm (8 to 12 inches) from surface. Apply in uniform thin coats. Never apply in thick coats. If recoating is desired, apply within 1 hour or after 48 hours.

For better results, prime surface with white primer. For extra protection, apply a coat of Corrostop Ultra protective finish 635-105.

After use: Invert can and spray for five seconds to avoid clogging.

To obtain more information on application methods, visit the website at www.corrostop.ca or call our customer service: 1-800-463-7426.

STORAGE AND TRANSPORTATION

Keep product in a dry and ventilated area, between 10 and 30°C (50 and 86°F).

DISPOSAL

Consult your municipality about proper disposal procedure of leftover product in accordance with the laws and environmental respect or give it to a neighbour or a friend, a recreational service or a non-profit organization. Do not pour down the drain.

SAFETY MEASURES

Read the Material Safety Data Sheet. Avoid contact with eyes. Keep out of reach of children. Use only in well ventilated areas. Do not intentionally breathe vapour.

FIRST AID TREATMENT: If in contact with eyes, rinse thoroughly with clear water. If swallowed, do not induce vomiting. Call poison centre or physician immediately.